Handling and bundling facilities

特徴 Features

TBM-AUTOMATIC BINDING MACHINE




TBM320E/220E



TBM5100E/570E



- 高速運転・高耐久性。 High speed and high durability
- •高いメンテナンス性。
- •短時間で番線セットが可能。 Easy work to charge wire
- ●各機種共通のパーツが多い。 Utilising common parts throughout any models
- 多彩なラインナップ。 A large assortment of models





TBM320L/220L



TBM550H



TBM5100L/570L



TBM5100LW/570LW



Sタイプ2重巻結束例 Example of binding (Double Wrapped and besides S type)



TBM5100LT/580LT



順次結束例/Example of binding (Continuously Wrapped (ype)

Model	形	式	TBM320L(E)/220L(E)	TBM550H	TBM5100LW/570LW	TBM5100L(E)/570L(E)	TBM5100LT/580LT
Bundling D.(max)	結束物最大径		φ120mm	φ300mm	φ500mm/φ350mm	φ550mm/φ450mm	φ600mm/φ350mm
Bundling D.(min)	結束物最小径		φ50mm	φ100mm	φ100mm	φ100mm	φ150mm
Guidetrack I.D.	ガイドトラック内径		200mm	500mm	1,000mm/700mm	1,000mm/700mm	1,000mm/800mm
Binding cycle	結束時間		2.5sec	6.5sec	12sec/9sec	8.5sec/7sec	12sec/10sec
Applicable wires	使用ワイヤー		3.2mm/2.6mm	5.5mm	5.5mm	5.5mm	5.5mm
Bundling material	主な用途		Bar 棒鋼	Bar 棒鋼	Bar,SBQ 棒鋼,特殊鋼	Bar,SBQ 棒鋼,特殊鋼	Bar,Shape 棒鋼,形鋼